IN ONLINE CERTIFICATIONS DIRECTORY

FPQU2.E64380 Optical Isolators - Component

Page Bottom

Optical Isolators - Component

See General Information for Optical Isolators - Component

SHARP CORP ELECTRONIC COMPONENTS AND DEVICES BU

E64380

1 ASAHI DAIMON-CHO FUKUYAMA-SHI, HIROSHIMA-KEN 721-8522 JAPAN

Double protection optical isolated switches, Model(s) 1S3021, 1S3022, 1S3023, 1S3052, 1S3063, 1S3064, 1S3083, 1S3084, 2SD11, 3SD12, 3SD12, 3SD21, 3SD22, 3SD23, 3SF11, 3SF13, 3SF21, 3SF23, 3SH11, 3SH13, 3SH21, 3SH23, 3ST11, 3ST12, 3ST21, 3ST23, 4SD11, 4SD21, 4SF11, 4SF21, 4SH11, 4SH21, 4ST11, 4ST21, PC123, PC1231, PC725V, PC815, PC845, PC900V, PC901V, PC910L, PC910S, PC911L, PC922, PC923, PC923L, PC924, PC924L, PC942, PC956L, PC957L, PC957S, R22MA1, R31MA1, R32MA1, S21ME6

Double protection optical isolated switches, providing 2500 Vac isolation, Model(s) PC3H2 (a), PC3H3 (a)

Double protection optical isolated switches, providing 2500 Vac isolation, Model(s) PC3H4#, PC prefix is optional, # - may be followed by suffix 4.

Double protection optical isolated switches, providing 2500 Vac isolation, Model(s) PC3H41 (marked H41) (a), PC3H5 (a), PC3H51 (marked H51) (a), PC3H7 (a), PC3H71 (marked H71) (a), PC4H51 (a), PC4H52 (marked 4H52) (a)

Double protection optical isolated switches, providing 3750 Vac isolation, Model(s) 3SS21, PC352 (a), PC353 (a), PC354 (a), PC355 (a), PC356 (a), PC364 (a), PC365 (a), PC367 (a), PC3HA7 (marked HA7) (a), PC3HU7 (a), PC400, PC401, PC410L, PC410S, PC411L, PC411S, PC412S, PC451 (a), PC452, PC456L, PC457L, PC457S, PC4D10S, S21MS3, S21MS4, S2S3 (marked 2S3), S2S4 (marked 2S4), S2S5 (marked 2S5)

Double protection optical isolated switches, providing 5000 Vac isolation, Model(s) PC713V, PC714V, PC715V, PC8110, PC812, PC8141, PC8151, PC817, PC8171, PC847

Double protection optical isolators having an isolation voltage of 5000 V ac, Model(s) PC3L57 (b), PC925L

Double protection optical isolators having an isolation voltage of 5000 Vrms, Model(s) PC851 (b)

Double protection optical isolators having an isolation voltage of 5300 Vrms, Model(s) PC123 (b), PC814(b), PC817 (b)

Optical isolated switches, Model(s) PC724V, PC814, PC844, PC851, PC852, PC853, PC853H


Optical isolated switches, providing 4000 Vac isolation, Model(s) PC928, PC929

(a) - PC prefix is optional.

Last Updated on 2017-05-04

(b) - May be followed by any letters or numbers.

Note - Q of PC507Q may be a square.



Questions?

<u>Print this page</u>

Terms of Use

<u>Page Top</u>

© 2018 UL LLC

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be

http://database.ul.本交由深圳市达靖科技有限您可整理归纳nan更多资料请的问shwiwe-Sztieltkplacom-+Component&objid=107

2018/4/16

FPQU2.E64380 - Optical Isolators - Component

presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2018 UL LLC".